



SYLVAC Digital Måletaster P12D 0-12,7 mmx0,01 µm med M8 tilslutning (High Resolution- 801.1212)

SYL8011212

- High-precision measuring probes with patented measuring system combining inductive and capacitive technologies
- Absolute system with integrated electronic error correction (no more pairing with the unit or computer) guaranteeing high accuracy over the entire measuring range
- Extremely robust ball bearing guide guarantees a minimum of 100 million cycles (30 millions with radial load)
- Stainless steel body Ø 12 mm, fixing diameter 8 h6
- Measuring range 12.7 mm
- Available in 3 versions: Standard, Work and Pro
- Measuring force selectable: low or very low for vertical use only
- Output signal in direct digital format without the need for a converter
- Reading speed up to 100 values per second depending on configuration
- Straight cable length 2m with either USB or M8 connector
- Cable outlet protected by a spring which can be tilted by 90° with the optional accessory 801-5101
- Protection class IP54

Produkt detaljer

| | |
|--------------|---------------|
| Varenr. | SYL8011212 |
| EAN | 7640125715552 |
| Toldtarif | 8466300000 |
| Salgskvantum | 1 |

Produktspecifikationer

| | |
|------------------------|---------------|
| Barcode | 7640125715552 |
| Aflæsning | 0,01 µm |
| Data udgang | M8 |
| Fejlgrænse | 0,6 µm |
| Gentagelsesnøjagtighed | 0,08 µm |
| IP Klasse | IP54 |
| Måleområde | 0-12,7 mm |
| Model | P12D HR M8 |
| Nøjagtighed | 0,6 µm |
| SYLVAC varenr. | 801-1212 |
| Varemærke | SYLVAC |
| Brutto vægt | 0,200 kg |
| Netto vægt | 0,200 kg |